

Post/ Column Size	MiTek Stock No.	Ref. No.	Steel Gauge		Dimensions (in)			Fastener Schedule ^{2,4}						DF/SP Allowable Loads (Lbs.) ³			Corrosion Finish	Code Ref.
			Base	Stand- off Plate	W	H	L	Anchor Bolt	Post				Bearing 100%	Uplift ¹				
									Nails		Bolts			Nails 160%	Bolts 160%			
								Qty	Dia. (in)	Qty	Type	Qty	Dia. (in)					
4 x 4	PA44-TZ	--	18	12	3-9/16	2-1/4	3-1/2	1	1/2	8	16d	--	--	4155	455	--	IBC, FL, LA	
	PA44E-TZ	--	18	16	3-9/16	3-1/2	3-1/2	1	1/2	6	16d	--	--	6775	1035	--		
	PAF44-TZ	ABA44Z	14	--	3-11/16	2-11/16	3-5/16	1	1/2	8	10d HDG	--	--	7245	810	--		
	PAU44	ABU44	12	16	3-9/16	5-7/16	3	1	5/8	12	16d	2	1/2	6775	2535	2265		
4 x 4 Rough	PA44R-TZ	--	18	12	4-1/16	2-1/2	4	1	1/2	12	16d	--	--	4155	455	--		
4 x 6	PA46	--	18	12	3-9/16	2-1/4	5-1/2	1	1/2	14	16d	--	--	4155	455	--		
	PA46E	--	18	12	3-9/16	3-1/2	5-1/2	1	5/8	8	16d	--	--	6775	1035	--		
	PAF46-TZ	ABA46Z	14	--	3-11/16	3-1/4	4-15/16	1	5/8	8	10d HDG	--	--	8490	1365	--		
											16d HDG	--	--	8835				
	PAU46	ABU46	10	12	3-9/16	6	5	1	5/8	12	16d	2	1/2	13815	2535	2265		
4 x 6 Rough	PA46R	--	18	10	4-1/16	3-1/2	6	1	1/2	14	16d		--	4155	455	--		
5 x 5 Rough	PA55R-TZ	--	16	12	5	3-5/8	5	1	1/2	8	16d HDG	--	--	4155	455	--	--	
6 x 6	PA66	--	18	12	5-1/2	2-7/8	5-1/2	1	1/2	16	16d	--	--	5930	250	--	IBC, FL, LA	
	PA66E	--	14	12	5-1/2	3-1/2	5-1/2	1	5/8	8	16d	--	--	16005	1130	--		
	PAF66-TZ	ABA66Z	14	--	5-11/16	3-1/4	4-15/16	1	5/8	8	10d HDG	--	--	10870	1375	--		
											16d HDG	--	--	12040				
	PAU66	ABU66	10	12	5-1/2	6	5	1	5/8	12	16d	2	1/2	16005	2455	2265		
6 x 6 Rough	PA66R	--	18	12	6-1/16	3-1/4	6-1/16	1	1/2	16	16d	--	--	5930	250	--		
	PA66ER-TZ	ABA66R	14	12	6	3-1/4	5-1/2	1	5/8	8	16d HDG	--	--	16005	1130	--		
	PAU66R-TZ	ABU66RZ	10	12	6-1/16	5-3/4	5	1	5/8	12	16d HDG	2	1/2	16005	1475	1475		
8 x 8	PAU88	ABU88	12	12	7-1/2	7-3/16	7-1/16	2	5/8	14	16d	--	--	24900	3315	--		
8 x 8 Rough	PAU88R	ABU88R	12	12	8-1/16	6-15/16	7-1/16	2	5/8	14	16d	--	--	24900	3315	--		
10 x 10	PAU1010	ABU1010	12	16	9-1/2	7-3/16	9-1/2	2	5/8	14	16d	2	5/8	27095	1495	1495		
10 x 10 Rough	PAU1010R	--	12	16	10-1/16	7-3/16	10	2	5/8	14	16d	2	5/8	27095	1495	1495		
12 x 12	PAU1212	ABU1212	12	12	11-1/2	6-7/8	11-1/2	2	5/8	18	16d	2	5/8	64015	1180	1180		
12 x 12 Rough	PAU1212R	--	12	12	12-1/8	6-7/8	12-1/8	2	5/8	18	16d	2	5/8	64015	1180	1180		

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) All bolts shall meet or exceed the specifications of ASTM A 307.

3) Allowable loads are based on the use of either nails or bolts; nail and bolt values cannot be combined.

4) **NAILS:** 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long.

New products or updated product information are designated in **blue font**.

Corrosion Finish Key ■ Stainless Steel ■ Gold Coat ■ HDG ■ Triple Zinc