


# DuPont™ FlexWrap™ EZ

## Extendable Self-Adhered Flashing For Sealing Around Non-Flanged Objects

DuPont™ FlexWrap™ EZ is a flexible, self-adhered tape with a 100% butyl-based adhesive layer that creates an air and water-tight seal around penetrations of all different shapes and sizes. DuPont™ FlexWrap™ EZ is available in a 2 3/4 in x 15-ft roll roll length to provide an option for home builders, trade contractors and remodelers to easily seal around non-flanged objects that penetrate the building envelope. It is ideal for flashing around many smaller wall protrusions like plumbing and HVAC components, vents, wires, exterior electrical outlets, exterior lights, and gas lines. DuPont™ FlexWrap™ EZ is a part of a complete DuPont™ Tyvek® Building Envelope Solution that helps to improve the energy efficiency and durability of buildings.

This bulletin provides installation guidance when the wall penetration rough opening (RO) is not more than 1/2" larger than the outside diameter/ dimension (OD) of the non-flanged product.



### General Considerations

For best results, install DuPont™ Tyvek™ Water-Resistive Barriers (WRB), or other water-resistive barrier before installation of a product that penetrates the exterior sheathing. Once in place and secured, the penetrating object can be sealed directly to the water-resistive barrier using DuPont™ FlexWrap™ EZ to establish continuity of the drainage plane.

*Please refer to the applicable DuPont Weatherization Systems Installation Guidelines for more information.*

Maintain careful placement of the exposed butyl during installation once the release paper is removed. DuPont recommends installers evaluate suitability of DuPont™ FlexWrap™ EZ onto non DuPont™ Tyvek® WRBs.

### Sealing Round Pipes, and Other Round Objects, with Outside Diameters (OD) Less Than 2"

1. Cut a piece of DuPont™ FlexWrap™ EZ that is 1/2 the length of the pipe circumference.
2. Fold the DuPont™ FlexWrap™ EZ to break perforations in release paper and create sharpe crease.
3. Remove narrow (~1") width of release paper.



4. While still folded, center DuPont™ FlexWrap™ EZ under the pipe and use the remaining release paper edge to position DuPont™ FlexWrap™ EZ tight against the WRB. Adhere the exposed butyl to the underside of the pipe.




5. Gently remove remaining release paper to avoid stretching the product.



## Sealing Round Pipes, and Other Round Objects, with Outside Diameters (OD) Less Than 2" (continued)

6. Fan out DuPont™ FlexWrap™ EZ so it extends onto the WRB



7. Cut a second piece of DuPont™ FlexWrap™ EZ the length of the pipe circumference.



8. Fold the second piece of DuPont™ FlexWrap™ EZ to break perforations in release paper and create a sharp crease. Remove narrow (~1") width of release paper. While still folded, center DuPont™ FlexWrap™ EZ above the pipe and use the remaining release paper to position tight against the WRB. Adhere the exposed butyl to the top, and down each side of the pipe to the 3 and 9 o'clock positions.



9. Extend the length of DuPont™ FlexWrap™ EZ and gently remove remaining release paper to avoid stretching the product.




10. Position the unadhered butyl of the narrow section below to overlap the edges of DuPont™ FlexWrap™ EZ installed first by a minimum of 1". Use thumbs to adhere. Do not stretch DuPont™ FlexWrap™ EZ.



11. Fan out the remaining unadhered DuPont™ FlexWrap™ EZ onto the WRB above and down each side of the pipe.



12. Use firm hand pressure on both pipe and WRB surfaces for a good bond and secure seal. Remove any wrinkles or creases by using firm hand pressure to ensure a fully adhered and smooth surface.



**Sealing Round Pipes, and Other Round Objects, with Outside Diameters (OD) Less Than 2" (continued)**  
**(Method can also be used for rectangular objects)**

1. Measure and cut a piece of DuPont™ FlexWrap™ EZ at least 2" longer than pipe circumference.



2. Fold the piece of FlexWrap™ EZ to break perforations in release paper and create a sharp crease.



3. Remove narrow (~1") width of release paper.



4. With the flashing still folded at the crease, use the remaining release paper edge to position FlexWrap™ EZ tight against the WRB at the 3 o'clock position and adhere a small section of the exposed butyl onto the pipe.




5. With the flashing still folded at the crease, extend length of FlexWrap™ EZ and gently remove remaining release paper. Avoid stretching FlexWrap™ EZ





6. Continue to adhere FlexWrap™ EZ around the circumference of the pipe to the 1 o'clock position by gently placing the exposed butyl onto the pipe surface with minimal tension.



7. Unfold and fan out FlexWrap™ EZ applied at the 3 o'clock position to the WRB. Adhere the remaining exposed butyl of FlexWrap™ EZ to lap over the layer below and then onto the WRB.



8. Fan out the remaining FlexWrap™ EZ onto the WRB around the circumference of the pipe. Use firm hand pressure on both pipe and WRB surfaces for a good bond and a secure seal. If any wrinkles or creases form during application, ensure they are smoothed out and adhered with firm hand pressure.




**The method for Round Objects with Outside Diameters (OD) Greater Than 2" can be used for non-flanged objects having rectangular and other geometries.**




1. Measure and cut a 2" length of DuPont™ FlexWrap™ EZ  
NOTE: Larger wires, cables, or bundles of wires may require a longer piece of DuPont™ FlexWrap™ EZ.



2. Fold the piece of FlexWrap™ EZ to break perforations in release paper to create a 90 degree angle.



3. Remove narrow (~1") width of release paper.



4. Position FlexWrap™ EZ above the wire so the exposed butyl is centered on top of the wire, and the side with remaining release paper is against the WRB.



5. Extend both sides of FlexWrap™ EZ below the wire and adhere each corner and outside edge to WRB as shown.



6. Pinch together the exposed butyl of FlexWrap™ EZ below wire to create a flap and complete a full perimeter seal around wire. Use firm hand pressure to remove any pinholes at the crease below the wire where the butyl is adhered together.



7. Remove remaining release paper.





**For more information visit  
[tyvek.com](https://www.tyvek.com) or call 1-800-448-9835.**

NOTICE: No freedom from infringement of any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business. CAUTION: This product is combustible and shall only be used as specified by the local building code with respect to flame spread classification and to the use of a suitable thermal barrier. For more information call the DuPont Contact Center at 866-583-2583 or contact your local building inspector. For emergencies contact Chemtrec 800-424-9300, CCN (Contract Number) 7442.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont.

43-D100783-enNA-0120